Cash Drawer

SUNMI Mini Cash Drawer

The high-toughness ABS matt panel is adopted which is rustless and won't hurt your hands.

Same capacity, reduced volume (by 22.5%) compared with traditional small cash drawers.

It can be opened with one press on the key for solid and smooth industrial bearings are used.

With wide-area voltage driven design it suits to 9V/12V/24V cash register output voltage.

Give you a neat work table with a cable storage compartment on the top.

Strengthened steel metallic clips covered by durable ABS is adopted for noise reduction.





10Kg bearable



1,000,000+ operations



Open interfaces



Customizable safety reminder



Three positions lock design

SUNMI Mini Cash Drawer

Technical specifications



Cash Drawer

Plastic and metallic



Trays

Four normal bill & one big bill trays
Three coin trays



Metallic Bearing

Up to 10kg bearable



Cable

RJ12, 6P4C, 0.8m



Lock

Three positions lock (electronic, manual and deadlock)



Bill Clip

Plastic and metallic



Cable Storage Compartment

Rear-set compartment with cover



Drive Voltage

DC9V~24V, 1A



Drive Pulse Width

100ms - 300ms



Drive Protections

Termal shutdown

3A overcurrent protection triggered by electromagnetic valve shrot circuit Input pulse overvoltage protection Input pulse timeout protection Self-adaptive to 9V-28V input voltage Contact ESD 8KV/air ESD 15KV



Service Life

≥1000000 operations



Noise

<50dB



Status Feedback

Status detection switch



Size

W317mm x L332mm x H72mm



Weight

23 Ka



Working Environment

Working temperature and humidity: 0° C ~ 45° C, 30° C ~ 85° Storage temperature and humidity: -20° C ~ 60° C, 10° C ~ 90°